

NAVIGATEWORX

NR600-5G



Industrial **5G** VPN Router, Dual SIM Failover,
High speed cellular 5G connectivity

Navigateworx NR600-5G industrial 5G VPN router enables wireless data connectivity over public and private 5G cellular networks.

NR600-5G router has dual SIM backup, 1 WAN and 3 LAN Ethernet ports, Dual band 2.4GHz and 5.8GHz Wi-Fi access, supports 9 to 48 VDC wide range power inputs, designed with reverse-voltage protection mechanism. It is an advanced choice for wireless M2M applications with reliable features for data transmission.

TYPICAL APPLICATION



Secure and reliable internet access

- Wireless Mobile Broadband **5G/4G/3G** Connection
- Connection manager ensure seamless communication
- Dual band 2.4GHz and 5.8GHz Wi-Fi access

Designed for industrial usage

- Power Input Range 9 to 48 VDC
- Industrial design for harsh environment
- Aluminum enclosure and wall mounting installation

Easy to use and easy maintenance

- User friendly web interface for user interaction
- Support Central Management Platform

SPECIFICATIONS

CELLULAR	
Frequency Bands	5G NR NSA: n1/n2/n3/n5/n7/n8/n12/n20/n25/n28/n38/n40/n41/n48*/n66/n71/n77/n78/n79 5G NR SA: n1/n2/n3/n5/n7/n8/n12/n20/n25/n28/n38/n40/n41/n48*/n66/n71/n77/n78/n79 4G LTE-FDD: B1/B2/B3/B4/B5/B7/B8/B12(B17)/B13/B14/B18/B19/B20/B25/B26/B28/B29/B30/B32/B66/B71 4G LTE-TDD: B34/B38/B39/B40/B41/B42/B43/B48 3G: B1/B2/B3/B4/B5/B6/B8/B19 More Bands Demands please contact with us
SIM	2 x SIM slots, 1.8V / 3V
SIM Failover	Auto-switch cases: data limited, no network, network denied, data connection fail
Antennas	4 external antennas, SMA
ETHERNET	
Number of Ports	1 x WAN + 3 x LAN, Auto 10/100/1000 Mbps
Magnet Isolation Protection	1.5 KV
DUAL BAND Wi-Fi	
Wireless Mode	802.11 a/b/g/n/ac 2*2 MIMO, supports AP and Client modes
Wireless Speed	5.8G: Up to 867Mbps 2.4G: Up to 300Mbps
Wireless Security	WPA, WPA2, WEP, CCMP, TKIP
Frequency Bands	5.15 – 5.825 GHz (5 GHz ISM band) 2.412 - 2.484 GHz (2.4 GHz ISM band)
Antennas	2 x RP-SMA
GNSS/GPS	
Features	Gen9C Lite of Qualcomm (GPS, GLONASS, BeiDou, Galileo)
Protocol	NMEA-0183
Antennas	1 x SMA female with 50 ohms impedance
POWER	
Connector	3-pin 3.5 mm female socket
Input Voltage Range	9 to 48 VDC
Power Consumption	Idle: TBD Data link: TBD
HARDWARE	
Built-in	Watchdog
LEDs	SYS, NET, USR, RSSI x 3
Reset Button	Reset/restore to factory default button
Ingress Protection	IP30
Housing & Weight	Aluminum, TBD
Dimensions	145 * 122* 54 mm
Installations	Din Rail
Operating Temperature	-30 °C to 70 °C
Extended Temperature	-40 °C to 85 °C
Operating Humidity	5% to 95% non-condensing
NETWORK	
Routing	Static routing
Network Protocols	TCP, UDP, IPv4, ICMP, NTP, DNS, HTTP, HTTPS, ARP, PPP, PPPoE, DHCP, IP Passthrough, VRRP
Connection Manager	Ping Detection, Timer Reboot, ICMP for link detection
Firewall	Flexible access control of TCP, UDP, ICMP packets, MAC address filter
DDNS	Supported some service providers, others can be configured manually
SMS	SMS Configuration, SMS Gateway, SMS Notification
VPN	
OpenVPN	OpenVPN server/client mode, client mode supports up to 5 x OpenVPN tunnels
GRE	Layer2 and Layer3, supports up to 5 x GRE VPN tunnels
IPsec	IKEv1, IKEv2, supports up to 5 x IPsec VPN tunnels

MONITORING & MANAGEMENT

Web GUI	HTTP/HTTPS, firmware upgrade
Command Line Interface	SSHv2 and TELNET
Management platform	Central Management Platform


APP CENTER

APPs	<p>VPN: L2TP, PPTP, DMVPN</p> <p>Network: Dynamic Routing (RIPv1/v2, OSPF, BGP), Email Notification, Enforce Modem PPP, QoS</p> <p>Management: AT over IP, AT over COM, AT over Telnet, SNMPv1/v2/v3/, TR069, DMPC</p> <p>Protocol Converter: Modbus Master, Modbus Slave, Modbus ID Mapping, Modbus Gateway</p> <p>IEC101-104, DLMS to IEC104, Modbus to DNP3</p> <p>More Apps Demands please contact with us</p>
------	---

APPROVAL

EMI	EN 55032:2012 Class B	
EMS	IEC 61000-4-2 ESD	Level 3
	IEC 61000-4-3 RS	Level 3
	IEC 61000-4-4 EFT	Level 3
	IEC 61000-4-5 Surge	Level 3
	IEC 61000-4-6 CS	Level 3
Vibration	EN50155	

DIMENSIONS



ORDERING INFORMATION

MODEL	PART NUMBER	DESCRIPTION
 NR600-5G	A614533	5G, Dual SIMs, 4 x Gigabit Port, Dual band 2.4GHz and 5.8GHz Wi-Fi, 9 - 48VDC
OPTIONAL ACCESSORIES		
 Power Supply	F001009	Power Supply Adapter, EU Plug, Input 100 to 240VAC, Output 12V DC 1.5A
	F001011	Power Supply Adapter, AU Plug, Input 100 to 240VAC, Output 12V DC 1.5A
	F001012	Power Supply Adapter, US Plug, Input 100 to 240VAC, Output 12V DC 1.5A
	F001013	Power Supply Adapter, UK Plug, Input 100 to 240VAC, Output 12V DC 1.5A
 5G Rubber Antenna	F001025	5G Rubber Antenna, 698-960/1710-3500MHz, 2.15dbi, Φ13×172mm
 5G Magnet Antenna	F001026	5G Magnet Antenna, 698-960/1710-3500MHz, 3dbi, 3m, Φ29×290mm
 Wi-Fi Rubber Antenna	TBD	TBD
 Wi-Fi Magnet Antenna	TBD	TBD
 GPS Antenna	F001015	GPS Active Magnetic Mount Antenna, 3 Meters Cable
 Din-Rail	F004001	Din Rail Kit, 35 mm, Aluminum with Black Spray Surface, 50 * 40 * 8.5 mm, 3 * M3.5 Screw Holes

ABOUT NAVIGATEWORX

ADDRESS: Room 608, North Side, 6th Floor, Building No. 5, Guangzhou Scientech Park, No.9 Lan Yu No.4 Street, Huangpu District, Guangzhou City, Guangdong Province, China

PHONE: +86-20-86669763
EMAIL: sales@navigateworx.com
WEB: www.navigateworx.com