

PX207W-J

7" TFT 1024x600 with
Intel Celeron CPU
Windows 10.0



Ordering Information

PX207WC-J1	7" Capacitive, Intel Celeron J1900
PX207WR-J1	7" Resistive, Intel Celeron J1900
PX207WC-J4	7" Capacitive, Intel Celeron J4125
PX207WR-J4	7" Resistive, Intel Celeron J4125

Hardware

Intel Celeron J1900 (2.0GHz), J4125 (2.0GHz)

8GB RAM, 64GB Flash

J1900: 1 x GbE RJ-45 (2xGbE option)

J4125: 2 x GbE RJ-45

1 x RS232 (422/485 option)

WiFi 2.4G & 5G, BT 4.0, (SIM/GPS option)

2 x USB 2.0, 2 x USB 3.0

1 x HDMI, 1 x VGA

1 x Line-out/Mic-in, 2 x built-in Speakers

Mechanical

Dimension 225 (W) x 160.7 (H) x 59.0 (D) mm

Net weight 1.9 (Kgs)

Cut-out 210.9 (W) x 146.5 (H)

Panel Mount, VESA 75x75/100x100

Aluminum front bezel and chassis

Display & Touch

7" TFT-LCD, 1024x600

Brightness 250 (cd/m²)

View angle 160/160 (H°/V°)

Backlight Lifetime 50,000 hours

Contrast 1000:1

Capacitive/Resistive touch

OS & Power

Win 10 / Linux

12~24VDC, < 48 watts

**Screw Locking

Terminal Block
Adaptor

Environmental

IP65 Front

Op. Temp -10°C ~ 50°C

Storage Temp. -20°C ~ 70°C

10% to 90% @ 40°C (non-condensing)

CE/FCC (EN 55022, EN 55024, EN 61000-3-2, EN 61000-3-3)

