

# PX211W-J

11.6" TFT 1920x1080 with  
Intel Celeron CPU  
Windows 10.0



## Ordering Information

PX211WC-J1	11.6" Capacitive, Intel Celeron J1900
PX211WR-J1	11.6" Resistive, Intel Celeron J1900
PX211WC-J4	11.6" Capacitive, Intel Celeron J4125
PX211WR-J4	11.6" Resistive, Intel Celeron J4125

## Hardware

Intel Celeron J1900 (2.0GHz), J4125 (2.0GHz)

8GB RAM, 64GB Flash

J1900: 1 x GbE RJ-45 (2xGbE option)  
J4125: 2 x GbE RJ-45

2 x RS232 (422/485 option)

WiFi 2.4G & 5G, BT 4.0, (SIM/GPS option)

2 x USB 2.0, 2 x USB 3.0

1 x HDMI, 1 x VGA

1 x Line-out/Mic-in, 2 x built-in Speakers

## Mechanical

Dimension 328.3 (W) x 216.3 (H) x 60.0 (D) mm

Net weight 2.3 (Kgs)

Cut-out 314.4 (W) x 202.4 (H)

Panel Mount, VESA 75x75/100x100

Aluminum front bezel and chassis (Black)

## Display & Touch

11.6" TFT-LCD, 1920x1080

Brightness 300 (cd/m<sup>2</sup>)

View angle 178/178 (H°/V°)

Backlight Lifetime 50,000 hours

Contrast 1000:1

Capacitive/Resistive touch

## OS & Power

Win 10 / Linux

12~24VDC, < 48 watts

## Environmental

IP65 Front

Op. Temp -10°C ~ 50°C

Storage Temp. -20°C ~ 70°C

10% to 90% @ 40°C (non-condensing)

CE/FCC (EN 55022, EN 55024, EN 61000-3-2, EN 61000-3-3)

